



RT2L



Specifications


Model Number	RT2L
Thread Types	Inch, Metric, Pipe, SAE, National
Threads	Male (Bolt), Female (Nut)
Works With	Grinder, Drill
Shank Size	1/4 inch (6.4 mm)
Head Diameter	3/4 inch (19 mm)
Overall Length	4 inch (100 mm)
Minimum Working ID	5/8 inch (15.9 mm)
Maximum Working OD	No Limit
Minimum Pitch	28 TPI (0.8 metric)
Thread Angle	60 degrees
RPM	Recommended 12,000 (Max 15,000)
Lube Recommend	Dry, Light Oil, or Mineral Spirits
PPE	Safety Glasses, Goggles, or Shield

ID = Inner Diameter • OD = Outer Diameter • RPM = Revolutions Per Minute • Metric measurements are the most actual sizes, inch measurements shown are rounded with the exception of arbor diameter • Lube will help flush area and prolong tool life • Non-flammable lubes are recommended. • PPE = Personal Protective Equipment

For safety, usage instructions, tips, videos, demos, and warranty details see additional resources online.

WARNING: This product may including Lead and/or Nickel, which are classed as P65 Warning for the state of California.
For more information: www.P65WARNINGS.ca.gov

www.rotarythread.com
PAT. US 10,183,372,B2



GRINDER / DRILL



WEAR SAFETY GOGGLES
USAR LENTES DE SEGURIDAD
PORTER DES LUNETTES DE SÉCURITÉ